Day Tanks

Diesel Director Packaged Day Tanks





UL 2085 FIRE RATED DAY TANKS

30 Year Warranty

True double-wall construction with lightweight concrete filled interstitial space

- UL 2085 listed and labeled protected aboveground tank for flammable and combustible liquids - fire, vehicle impact and ballistic rated
- Meets requirements for secondary containment, leak monitoring, spill containment, and overfill protection
- Inner and outer tanks constructed per UL 142 Steel aboveground tanks for flammable and combustible liquids
- Six inches of lightweight concrete protection between inner and outer tanks provides minimum two-hour fire rating
- High-build polyester epoxy glassflake impregnated coating used for saltwater submersion protection on offshore platforms, 20,000 hour ASTM B117 salt spray tested
- Primary and emergency vents standard
- All fittings and protrusions are stainless steel

UL 142 DOUBLE WALL DAY TANKS

Steel aboveground tanks for flammable and combustible liquids

- UL 142 listed and labeled protected aboveground tank for flammable and combustible liquids
- Meets requirements for secondary containment, leak monitoring, spill containment, and overfill protection
- No external cross beams or side supports to interfere with generator placement or stairs and walkways
- Primary and emergency vents standard
- Rounded corners allowing proper adherence of industrial grade enamel coating
- Steel support channels allow visual tank bottom inspection and air circulation



Diesel Director Day TanksReliable Fuel Storage and Delivery Systems for Diesel Engine Generator Sets

- Supply & return pumps
- Control panel with high and low level alarms
- Leak sensor
- Emergency and primary vents
- Gauge stick

- Float fuel level
- Mechanical leak sensor
- Spare fittings
- Tank drains with ball valve
- Lockable fill cap

- Phoenix Products coating system
- Optional OSHPD certification
- Steel support channel allow visual tank bottom inspection and air circulation