

# PowerTank

Double-Wall Secondary Containment Sub-Base Tanks



phoenixproducts



## DOUBLE-WALL GENERATOR SUB-BASE FUEL TANKS

### Steel aboveground sub-base tanks for flammable and combustible liquids

- UL 142 listed and labled – inner and outer tanks are completely enclosed and pressure tested
- Meets requirements for secondary containment, leak monitoring, spill containment, and overfill protection
- No external cross beams or side supports to interfere with generator placement or stairs and walkways
- Supports generator sets up to 80,000 pounds, with or without enclosures
- Primary and emergency vents standard
- Rounded corners allowing proper adherence of industrial grade enamel coating
- Steel support channel allow visual tank bottom inspection and air circulation



### Designed to meet or exceed national, state and local codes

- NFPA 30, 30A, 37 & 110
- True double-wall construction for UL Certification
- Exceeds liability insurance requirements
- Engineered for seismic rating
- Earthquake and hurricane tie downs
- Leak detection space provided

phoenixproducts™

1727 Bennett Street, Jacksonville, FL 32206 • 904-354-1858 • 904-354-7929 Fax  
phoenix.sales@phoenixprods.com • www.phoenixprods.com



### Options

- Stairs and platforms (aluminum/galvanized steel) meeting OSHA standards with handrails
- Cold weather heaters
- Stainless steel inner and outer tanks
- Custom color matching
- Over-fill spill protection
- Fuel polishing systems
- Dispensing equipment
- Fuel monitoring and control systems
- Daytanks with supply and return pumps
- Tank top guard rails approved by OSHA

